THE CORPORATION OF THE TOWN OF HAWKESBURY

BY-LAW N° 59-2012

A By-law on Backflow prevention

WHEREAS subsection 11 (2) (6) of the *Municipal Act, 2001*, as amended, authorizes a municipality to pass by-laws respecting health, safety and well-being of persons;

AND WHEREAS subsection 11 (3) (4) of the *Municipal Act, 2001*, as amended, authorizes a municipality to pass by-laws respecting public utilities;

AND WHEREAS section 445 of the *Municipal Act, 2001*, as amended, states that if a municipality is satisfied that a contravention of a by-law of the municipality passed under this Act has occurred, the municipality may make an order requiring the person who contravened the by-law or who caused or permitted the contravention or the owner or occupier of the land on which the contravention occurred to do work to correct the contravention;

AND WHEREAS section 446 of the *Municipal Act, 2001,* as amended, states that if a municipality has the authority under this or any other Act or under a by-law under this or any other Act to direct or require a person to do a matter or thing, the municipality may also provide that, in default of it being done by the person directed or required to do it, the matter or thing shall be done at the person's expense;

AND WHEREAS the Municipal Council deems expedient to adopt a by-law to regulate cross-connections for the protection of its Potable water.

NOW THEREFORE, the Municipal Council of the Corporation of the Town of Hawkesbury enacts as follows:

1. DEFINITIONS

Authorized Functions List means the list of functions and the persons authorized to carry out such functions, as outlined in Schedule "A" hereto and as amended:

Backflow means the reversal of the normal direction of the flow of water;

Backflow Preventer means a device that prevents Backflow;

Building shall have the same definition of "building" in the Ontario *Building* Code Act, 1992, as amended;

Building Code Act means the Ontario Building Code Act, 1992, S.O. 1992, Chapter 23, as amended;

Building Code means Ontario Regulation 350/06, as amended;

Chief Building Official means the employee or his/her designate appointed by the Council to administer and to enforce the present By-law;

Council means the Municipal Council of the Corporation of the Town of Hawkesbury;

CSA B64.10/B64.10.1 means the document entitled "Selection and installation of Backflow Preventers / Maintenance and field testing of Backflow Preventers" by the Canadian Standards Association, as amended;

Cross-connection means any actual or potential connection between a Potable water system and any source of pollution or contamination and includes any by-pass, jumper connections, removable sections of pipe, swivel or changeover devices, and any other temporary or permanent connection arrangements through which Backflow can occur;

Cross-connection survey means a report that shall include existing or recommended Backflow Preventers, assessment of the degree of hazard, cross-connections discovered, corrective measures and recommendations, and a schedule of work to be completed, and any other relevant information;

High or severe hazard means any type of cross-connection or potential cross-connection involving water that has additives or substances that, under any concentration, can create a danger to health, as outlined in Schedule "D" hereto, as amended;

Minor hazard means any type of cross-connection or potential cross-connection that involves a substance that constitutes a nuisance and that results in a reduction in only the aesthetic qualities of water, as outlined in Schedule "D" hereto, as amended;

Moderate hazard means any minor hazard connection that has a low probability of becoming a severe hazard. This category includes, but is not limited to, connections involving water where the aesthetic qualities of the water have been reduced and, under certain conditions, can create a danger to health, as outlined in Schedule "D" hereto, as amended;

Municipal Drinking Water System means the Town's system of works, excluding plumbing, that is established for the purpose of providing users of the system with drinking water and that includes:

- (a) anything used for the collection, production, treatment, storage, supply or distribution of water,
- (b) anything related to the management of residue from the treatment process or the management of the discharge of a substance into the natural environment from the treatment system, and
- (c) a well or intake that serves as the source or entry point of raw water supply for the system.

Owner means any person, firm, or corporation having control over a property to which this By-law applies;

Potable water means water safe for human consumption;

Premises isolation means isolation of the water located within a Building or structure from the Municipal Drinking Water System;

Operating Authority means the Corporation of the Town of Hawkesbury, including its employees, servants and agents, in respect of the operation, management, maintenance or alteration of the Municipal Drinking Water System.

2. GENERAL PROVISION

This By-law shall apply to all industrial, commercial, institutional and multiresidential Buildings and structures existing at the time of adoption of this Bylaw and new ones, except Buildings of residential occupancies within the scope of Part 9 of the Ontario *Building Code*.

3. CONTAMINATION AND BACKFLOW PREVENTION

- 3.1 No Owner shall connect, cause to be connected, or allow to remain connected to the Municipal Drinking Water System any piping, fixture, fitting, container, or appliance that, under any circumstances, might allow any untreated water, waste water, pollutant, or any other liquid, chemical, or substance to enter the Municipal Drinking Water System.
- 3.2 No Owner of a property to which this By-law applies shall fail to ensure that a Backflow Preventer is installed in every Building or structure connected to the Municipal Drinking Water System.

4. REQUIRED SURVEYS

4.1 A Cross-connection survey of the plumbing systems on all new industrial,

commercial, institutional, and multi-residential Buildings and structures, except Buildings of residential occupancies within the scope of Part 9 of the Ontario *Building Code*, shall be completed at the Owner's expense by the approved personnel specified in the Authorized Functions List at least once and thereafter upon notification by the Operating Authority. For existing industrial, commercial, institutional, and multi-residential buildings, a Cross-connection survey shall be completed upon request by the Operating Authority.

- 4.2 The cross-connection survey shall be completed along with a report and sent to the Operating Authority within 30 days of the date of the request or before the issuance of the partial occupancy permit.
- 4.3 A cross-connection survey may be required upon change of use or at the discretion of the Operating Authority.
- 4.4 Upon identification of high or severe hazard, the approved company or person as prescribed in the Authorized Function List and/or the Owner shall, within 24 hours, notify in writing the Operating Authority.

5. SELECTION AND INSTALLATION OF BACKFLOW PREVENTERS

The selection and installation of Backflow Preventers shall be in accordance with the Ontario *Building Code Act*, 1992.

Backflow Preventers shall be installed within the timeframe below depending to the degree of hazard:

High or severe hazard Within 30 days from the date of identification of

hazard

Moderate and minor

Moderate and minor

hazard

Within 90 days from the date of identification of

hazard

6. INSPECTION FOR CROSS-CONNECTIONS - ACCESS

6.1 The Operating Authority shall be allowed access, with reasonable notice, to any premises connected to the Municipal Drinking Water System for the purpose of performing inspections to locate possible cross-connections. The Operating Authority may request a routine cross-connection inspection of the premises to be performed at the Owner's expense by an approved company or person as described in the Authorized Functions List.

- 6.2 The Operating Authority shall be allowed access, with reasonable notice, to any premises connected to the Municipal Drinking Water System for the purpose of performing inspections to verify compliance with section 9.
- 6.3 Where the access requirements of sections 6.1 and 6.2 are not fulfilled, a written notice may be issued by the Operating Authority outlining a revised deadline for access to the premises in question. If access is not provided by this deadline, the Operating Authority may, at its discretion, shut off the supply of water to the premises until the access is provided.
- 6.4 If a condition is found to violate section 3, the Operating Authority may immediately carry out an inspection at the Owner's expense, may issue any notice required to obtain compliance with section 3 and may shut off the supply of water to the premises.

7. NOTICES AND ORDERS TO CORRECT CROSS-CONNECTIONS

If the Owner to whom the Operating Authority has issued notice fails to comply with that notice, the Operating Authority may:

- a) give further notice to the Owner to correct the fault at his/her expense within a specified time period; if the notice is not complied with, the Operating Authority may then shut off the water service and have the necessary works or repairs done at the Owner's expense;
- b) issue and order, citing unsafe conditions, in accordance with the Ontario Building Code Act, 1992, as amended to correct the condition that could be hazardous to the health or safety of persons in the normal use of the Building, persons outside the Building, or person whose access to the Building has not been reasonably prevented; or
- c) without notice to the Owner, shut off the water service where the Operating Authority has determined, in its sole discretion, that an immediate threat of contamination to the Municipal Drinking Water System exists that can endanger public health or safety.

8. PREMISES ISOLATION

8.1 Where, in the opinion of the Operating Authority, a risk of possible contamination of the Municipal Drinking Water System exists, the Owner, on notice from the Operating Authority, shall install Premises isolation in addition to any other Backflow protection devices on the premises.

- 8.2 Notwithstanding subsection 8.1, Premises isolation shall be installed:
 - ➢ in Buildings of high or severe hazard in accordance with the Premises isolation requirements outlined in the Ontario Building Code Act, 1992; or
 - as required by the Operating Authority.

9. MAINTENACE AND FIELD-TESTING OF BACKFLOW PREVENTERS

- 9.1 Backflow Preventers shall be inspected and tested at the Owner's expense by the approved personnel specified in the Authorized Functions List to demonstrate that the devices are in proper working condition.
- 9.2 Inspection and testing of Backflow Preventers and frequency shall be done in accordance with the Schedule "B" attached hereto and reporting on the forms attached hereto as Schedule "C" or other forms acceptable to the Operating Authority.
- 9.3 Upon initial installation of Backflow Preventers, test reports shall be submitted to the Operating Authority within ten (10) days. Reports thereafter shall be made available on site for review as required by the Operating Authority and shall be kept for a period of not less than seven years.
- 9.4 When the results of the inspection and test in section 9.1 demonstrate that a Backflow Preventer is not in proper working condition, the Owner shall make all necessary repairs or replace the device within 5 days.
- 9.5 If the Owner does not make the appropriate repairs or replace the defective device within 5 days, the Operating Authority may issue a notice under section 6.4 or may shut off the water service or have the necessary works or repairs done at the Owner's expense.
- 9.6 If the Owner fails to have a Backflow Preventer tested, the Operating Authority may notify the Owner that the Backflow Preventer must be tested within a specified time.
- 9.7 If the Owner fails to have a Backflow Preventer tested within the specified time in the notice described in section 9.6 the Operating Authority may shut off the water service until the Backflow Preventer has been tested and approved as required by section 9.1 or may have it tested by an approved company or person as described in the Authorized Functions List at the Owner's expense.
- 9.8 Failure to comply with sections 9.1 to 9.5 can result in penalties as

described in section 14.

10. REMOVAL OF BACKFLOW PREVENTERS

No person shall remove a Backflow Preventer or any part thereof after it has been installed, and no Owner of a Building or structure in which a Backflow Preventer is installed shall cause or permit the removal of such a device, unless the purpose of such removal is to:

- facilitate the repair of the device, with the device replaced immediately after the repair is carried out;
- b) replace the device with another device that meets or exceeds the provision of this By-law; or
- c) remove a device when a fixture or equipment has been taken out of service and removed.

11. BACKLOW TEST EQUIPMENT MAINTENANCE

Where required by the Ontario *Building Code Act, 1992* and the CSA B64.10.1, all equipment used to test Backflow Preventers shall be verified or calibrated for accuracy.

12. AUTHORIZED FUNCTIONS

Only those persons listed in the Authorized Functions List shall carry out the corresponding functions set out in such list.

13. ENFORCEMENT

This By-law shall be enforced by the Chief Building Official or any other person appointed by the Council.

14. PENALTIES

Every person who contravenes any of the provisions of this By-law is guilty of an offence and is liable to the fine provided for under the *Municipal Act*, 2001, as amended.

Every person who contravenes any of the provisions of this By-law is guilty of an offence and upon conviction thereof is liable to a minimum fine of not less than Five Hundred Dollars (\$500.00) and not more than Twenty-Five Thousand Dollars (\$25,000.00). For continuous offences, the minimum fine shall be Five Hundred Dollars (\$500.00) and not more than Ten Thousand Dollars (\$10,000.00) for each day or part of a day that the offence continues.

A director or officer of a corporation who knowingly concurs in the contravention of this By-law by the corporation is guilty of an offence and upon conviction is liable to a minimum fine of not less than Five Hundred Dollars (\$500.00) and not more than Fifty Thousand Dollars (\$50,000.00). For subsequent convictions for the same offence, the minimum fine shall be One Thousand Dollars (\$1,000.00) and the maximum fine One Hundred Thousand Dollars (\$100,000.00).

VALIDITY

If a court of competent jurisdiction declares any provision, or any part of a provision of this By-law to be invalid, or to be of no force and effect, the provision shall be deemed conclusively to be severable from this By-law.

No part of this By-law not declared by a court of competent jurisdiction to be invalid shall be affected by the provision severable from this By-law.

16. ENACTMENT

THAT this By-law shall come into force and effect on the date of its adoption.

READ A FIRST, SECOND AND ADOPTED UPON THIRD READING THIS 27th DAY OF AUGUST 2012.

René Berthiaume, Mayor

Christine Groulx, Clerk

THE CORPORATION OF THE TOWN OF HAWKESBURY BY-LAW N° 59-2012 Schedule "A"

AUTHORIZED FUNCTIONS LIST

Lawn irrigation system installer with tester's licence	1	I	I	ĺ	ı	7
Fire system sprinkler fitter with a tester's licence	ı	I	1	[7	I
Apprentice plumber with tester's licence‡	I	7	7	7	~	>
Journeyman plumber with tester's licence†	7	7	٨	٨	٨	7
Licensed master plumber with contractor's and tester's licence	7	7	٨	٨	7	7
Certified engineering technologist with tester's licence*	7	I	٨	٨	٨	٨
Professional engineer with tester's licence	7	I	7	7	7	٨
Authorized function	Carry out cross-connection survey	Install, relocate, or replace Backflow Preventer	Repair Backflow Preventer	Test Backflow Preventer	Complete Items 1, 2, 3 and 4 in relation to fire protection systems	Complete Items 3 and 4 in relation to lawn sprinkler systems
Item	-	2	м	4	2	9

Required to be under the direction of a professional engineer.
 Required to be employed by a licensed plumbing contractor or licensed fire sprinkler contractor.
 Required to be employed by a licensed plumbing contractor and under the direct supervision of a journeyman plumber of master plumber.

THE CORPORATION OF THE TOWN OF HAWKESBURY BY-LAW N° 59-2012 Schedule "B"

Frequency requirements

Backflow Preventers shall be inspected and tested:

- a) upon installation;
- b) when cleaned, repaired, or overhauled;
- c) when relocated;
- d) annually, and;
- e) as required by the Operating Authority.

THE CORPORATION OF THE TOWN OF HAWKESBURY BY-LAW N° 59-2012 Schedule "C"

Reporting forms

						uble c	heck	nd ins valve ssure v	backfl	ow p	reve		Mailin	DC ^V	VA, PVB
Loca	tion address								Occupa	int					
Own	ner of device			-											
Own	ner contact											Tel	ephone	1 1 1-1	1 1 1
Owr	ner address			30000011100									l	Postal code	1 1 1
Name of certified tester Tester certification number					er		Tel	ephone	1 1 1-1	1 1 1					
Busi	ness name						Busin	ess address	5					Postal code	
Mak	e of test kit			Mode	numbe	r			Serial	numbe	r		Calib	ration due date	
	D	ouble	che	ck va	lve b	ackflo	w p	revente	er/Pre	ssure	vac	uum l	breaker		
	e of device	Make	e of dev	vice				Model r	number			Se	rial number		Size
	ation of device in build	ding													
Тур	ype of test							kPa □ psi □							
	D Check v		chec	k valv	e bac	kflow Checl							Pressure breal		
Test	With flow Leaked Closed tight	Ag	ainst flo eaked losed ti		With flow Ag.		□ Leak □ Clos	st flow ed ed tight	□ P				Check valve Leaked Closed tight	Test results Passed Failed	
	Pressure drop across check valve —			psi	90	Pressur across	check	valve			kPa □ psi □		kPa □ psi □	Pressure drop across check valve _	kPa □ psi □
			e fai	ls the	test	for a	ny r	eason,	compl	ete t	his s	ectio	n and note i	epair below	
Rea	ison for failure (if appa	arent)													
	Do Check v			valve	back	flow p		nter Theck va	lve 2				Pre	ssure vacuum breaker	
Repairs	35 Cleaned R 36 Disc 37 Spring 38 Guide 39 Pin Retainer 40 Hinged Pin 41 Seat 42 Diaphragm 43 Other, describe	t eplace	d	44 Cleaned Replaced 45 Disc 46 Spring 47 Guide 48 Pin Retainer 49 Hinged Pin 50 Seat 51 Diaphragm 52 Other, describe above				S3 □ Cleaned Replaced S4 □ Vent Disc S5 □ Vent Spring S6 □ Poppet S7 □ Retainer S8 □ Spring S9 □ Disc 60 □ Guide 61 □ Other, describe above							
	Date of re-test		YY	ММ	DD										
Re-test	With flow Leaked Closed tight	□ Lea	nst flov iked ised tig			h flow ked sed tight		Against f Leaked Closed			t result assed ailed		Air inlet valve Failed to open Opened at	Check valve Leaked Closed tight	Re-test results Passed Failed
Re	Pressure drop across check emarks			ki	Pa□ si□	Pressu	re dro s check	p (kPa E psi E		kPa □ psi □	Pressure drop across check	kPa □ psi □
	I certify that I ha		d the at	oove de	vice in	accordar	ice wit	h the City	of	T 121		Bylaw			
Sig	gnature registered tes	ter		,						YY	L MM	DD	Distribution White - Cross-c	onnection control office	
Fo	or office use only									YY	MM	1 DD		ant or owner	

Figure 1(a) Sample testing and inspection report for DCVA backflow preventers and PVB devices (See Clause 4.3.1.)

			Red	Test uced pr	ing and ins essure princi	pect ple b	ion rep ackflow	ort preventer	Mailin	g address		RP
Locat	ion address					Occup	oant					
Owne	er of device											
Owner contact								Telephone	1-1-	-		
Owner address										Postal code		
Nam	e of certified tester			Tester certification	numbe	er .	Telephone	ユーレ	-		i	
Busir	ness name				Business address					Postal code		Ī
Make	e of test kit	N	Aodel nu	umber		Seria	al number		Calib	ration due date		
			Red	duced p	ressure princ	ciple !	backflov	v preventer				
Mak	e of device		Model	number			Serial nur	mber		Size		
	ation of device in building				W 1414	DD	Sh. h. alf	☐ Leaked		ne pressure		kPa □
Туре	e of test Initial Annual		Date of	test	YY MM		Shut-off valve no. 2	☐ Closed tight		cirie pressure		psi □
Differential pressure Check valve 1 Check valve 2 relief valve												
Test	☐ Failed to open ☐ Le ☐ Opened at kPa psi ☐ Cl				Leaked Closed tight			☐ Leaked ☐ Closed tigl	ht			Test results
				first check	ck valve (no flow) psi			kPa □ psi □	☐ Passed ☐ Failed			
			the	test for	any reason,	comp	olete this	s section and	d note	repair belo	w	
Rea	ison for failure (if apparent))										
	Differential p											nut-off alve 2
1 Cleaned Replaced Replaced 2 Disc upper 8 Diaphragm small 14 Disc Disc lower 9 Upper 15 Sprii 4 Spring 10 Spacer 16 Cluic Cleaned 17 Pin 16 Cluic Cleaned 17 Pin 18 Hings 18					Check valve 1			Check v	alve 2			
Repair	Replaced 2 Disc upper 8 Disc Disc Disc Disc Disc Disc Disc Disc	pper pacer eat		13 🗆 Clean Repl: 14 🗆 Disc 15 🗀 Sprin 16 🗀 Guid 17 🗀 Pin re 18 🗀 Hing 19 🗆 Seat	ned aced 20 □ Diap g 21 □ Othe e etainer		ibe above)	22 Cleaned Replaced 23 Disc	29 🗆 Diaph	ragm (describe above)	31 🗆 (3 32 🗆 (3 33 🗆 (3 34 🗆 (4	Cleaned Replaced Disc Seat
_	Replaced 2 □ Disc upper 8 □ Disc Upper 9 □ U 4 □ Spring 10 □ Sp 5 □ Diaphragm Ig. 11 □ Se 6 □ Upper 12 □ O 7 □ Lower □ Failed to open	pper pacer eat		Repl. 14 Disc 15 Sprin 16 Guide 17 Pin re 18 Hing 19 Seat	g 21 Oth e etainer ed pin		ibe above)	22 Cleaned Replaced 23 Disc 24 Spring 25 Guide 26 Pin retainer 27 Hinged pin	29 □ Diaph 30 □ Other	ragm (describe above)	31 🗆 (3 32 🗆 (3 33 🗆 (3 34 🗆 (4	Cleaned Replaced Disc Seat Other (describe
Re-test Repair	Replaced 2 □ Disc upper 8 □ Disc Upper 9 □ U 4 □ Spring 10 □ Sp 5 □ Diaphragm Ig. 11 □ Se 6 □ Upper 12 □ O 7 □ Lower □ Failed to open	pper bacer eat other (describe	e above) —psi	Repl. 14 Disc 15 Sprin 16 Guidd 17 Pin re 18 Hing 19 Seat	ed aced 20 □ Diag g 21 □ Oth e etainer ed pin	er (descri	kPa □psi □	22 Cleaned Replaced 23 Disc 24 Spring 25 Guide 26 Pin retainer 27 Hinged pin 28 Seat Leaked Closed tigl	29 Diaph 30 Other	(describe above)	31 🗆 (3 32 🗆 (3 33 🗆 (3 34 🗆 (4	Cleaned Replaced Disc Seat Other (describe above) Re-test
Re-test	Replaced 2 □ Disc upper 8 □ Disc Upper 9 □ U 4 □ Spring 10 □ Sp 5 □ Diaphragm Ig. 11 □ Se 6 □ Upper 12 □ O 7 □ Lower □ Failed to open □ Opened at □ Disc Upper □ Disc	pper pacer eat other (describe	e above) —psi	Repl. 14 Disc 15 Sprin 16 Guidd 17 Pin re 18 Hing 19 Seat	ed aced 20 Diag g 21 Othe e etainer ed pin eked seed tight	er (descri	kPa □	22 Cleaned Replaced 23 Disc 24 Spring 25 Guide 26 Pin retainer 27 Hinged pin 28 Seat Leaked Closed tigl	29 Diaph 30 Other	(describe above)	31	Cleaned Replaced Disc Seat Other (describe above) Re-test results
Re-test	Replaced 2 □ Disc upper 8 □ Disc lower 9 □ Ul 4 □ Spring 10 □ Sp. 5 □ Diaphragm Ig. 11 □ Se. 6 □ Upper 12 □ O 7 □ Lower □ Failed to open □ Opened at □ Date of re-test	pper oacer eat ther (describe	e above) —psi DD	Repli 14 Disc 15 Sprin 16 Guid 17 Pin re 18 Hing 19 Seat	eed 20 Diag g	s	kPa □	22	29 Diaph 30 Other	(describe above)	31	Cleaned Replaced Disc Seat Other (describe above) Re-test results
Re-test	Replaced 2 Disc upper 8 Di 3 Disc lower 9 U 4 Spring 10 St 5 Diaphragm lg. 11 St 5 Compared 12 O T Lower Failed to open Opened at Date of re-test	pper oacer eat ther (describe	e above) —psi DD	Repli 14 Disc 15 Sprin 16 Guid 17 Pin re 18 Hing 19 Seat	eed 20 Diag g	s	kPa □	22 Cleaned Replaced 23 Disc 24 Spring 25 Guide 26 Pin retainer 27 Hinged pin 28 Seat Leaked Closed tigl	29 Diaph 30 Other	(describe above)	31	Cleaned Replaced Disc Seat Other (describe above) Re-test results
Be-test	Replaced 2 □ Disc upper 8 □ Disc lower 9 □ Ul 4 □ Spring 10 □ Sp. 5 □ Diaphragm Ig. 11 □ Se. 6 □ Upper 12 □ O 7 □ Lower □ Failed to open □ Opened at □ Date of re-test	pper oacer eat ther (describe	e above) —psi DD	Repli 14 Disc 15 Sprin 16 Guid 17 Pin re 18 Hing 19 Seat	eed 20 Diag g	s	kPa 🗆 psi 🗅	22	29 ☐ Diaph 30 ☐ Other tht rential acr raive (no	oss flow)	31 0 0 1 32 0 1 33 0 34 0 0 1 4 1 1 1 1 1 1 1 1	Cleaned Replaced Disc Seat Other (describe above) Re-test results

Figure 1(b)
Sample testing and inspection report for RP backflow preventers
(See Clause 4.3.1.)

	Testing and inspection report RP, DCVA, PVB, SRPVB Reduced pressure principle backflow preventer, double check valve backflow preventer, pressure vacuum breaker, and spill-resistant pressure vacuum breaker											
Location add	ress		spin-i	esista	Occupa		m b	reaker	Party contacted		Telephone num	
Owner	Owner Address of owner						Postal code Telephor					
Type of devic	e CVA PVB :	Make of device Model number			nber	Sei	rial number		Size	Install date	-	
Location of d	evice (i.e., building	g, room number)					Ins	stalled on wha	at system			
Tester's certification number				er		Business	name		Telephone numb			
8	of test (please check one) Initial					o flow) kPa [] psi [] = 8u		kPa □ □ psi □ kPa □ □ psi □				
-		Redu Double check v	ced pressure			preventer	_			Pressure vacua or spill-resista		Test
Test date	Check valve With flow Leaked	Against flow	Shut-off valve 2		Check valv With flow eaked	Against fl	ow		ntial pressure lief valve	Air inlet valve		results □ Passed
YY MM DD	Closed tight Pressure drop across check valve	☐ Closed tight	☐ Leaked ☐ Closed tig	ht Pres	closed tight sure drop sss check valv	☐ Closed ti	-	☐ Failed to d☐ Opened a		☐ Opened at	Closed tight	Failed
			If the device	falls th	e initial tes	t for any rea	son,	complete t	his section and	note repair below		
	1 Cleaned Replaced 2 Disc		20 Cleane Repla	ced	☐ Cleaned Replaced Disc	1		50 Clear Repl	aced	70 Cleaned Replaced 71 Vent disc		
Repairs	3 Spring 4 Guide 5 Pin retaine 6 Hinge pin 7 Seat 8 Diaphragr 9 Other (de:	n	22 Seat 23 Other (descr	32 33 34 35 36 37	Spring Guide Pin retair Hinge pir Seat Diaphrag Other (de	n gm		52 Disc, 53 Sprir 54 Diap 55 Upp 56 Low	lower ng hragm, large er er hragm, small	72 Vent spring 73 Poppet 74 Retainer 75 Spring 76 Disc 77 Guide 78 Other (descr	ibe)	Results
Re-test		,						59 Lowe 60 Space 61 Other				Re-test results
Re-test date	☐ Leaked ☐ Closed tight ☐	□ Leaked □ Closed tight	☐ Leaked	1.00	Leaked Closed tight	☐ Leaked☐ Closed ti	ght	☐ Failed to	open kPa	☐ Failed to open kP☐ Opened at ps	a□ □ Leaked i □ □ Closed tigh	☐ Passed
	Pressure drop across check valv	kPa □	☐ Closed ti	aht Pres	ssure drop oss check val		a 🗆	☐ Opened	atpsi [Pressure drop across check valve	kPa □ psi □	-
Remarks – r	eason for failure (it	f apparent)	-									
I certify tha Bylaw	t I have tested the	above device in a	ccordance wit	n the City	of		ignat	ture of certifie	ed tester		Date	MM DD
For office u	se only											
Distribution	: White - Cross-co	onnection control	officer				Cana	ry – Certified	tester	Pi	nk – Occupant or	owner

Figure 1(c) Sample testing and inspection report for RP and DCVA backflow preventers and PVB and SRPVB devices

(See Clause 4.3.1.)

5 Backflow prevention device testers

To be qualified, a backflow prevention device tester shall have completed and passed a cross-connection control course in backflow preventer testing.

The tester shall ensure that his or her knowledge and expertise remain current.

Note: In Canada, the authority having jurisdiction might require that schools or colleges providing certification services demonstrate their competence by obtaining accreditation in accordance with Annex B.

THE CORPORATION OF THE TOWN OF HAWKESBURY BY-LAW N° 59-2012 Schedule "D"

Guide to degree of hazard

Table B.1 **Guide to degree of hazard** — **Point of use cross-connections** (See Clauses 5.4.1 and B.2.)

Source of pollution or contamination	Degree of hazard
Agricultural chemical (sprayer)	Severe
Air compressor oil cooler	Moderate
Animal watering	Moderate
Aspirator (non-toxic)	Moderate
Aspirator (toxic)	Severe
Autoclave	Severe
Autopsy and mortuary equipment	Severe
Auxiliary water supply	Severe
Baptistery	Moderate
Basin	Moderate
Bathtub (all)	Moderate
Bedpan washer	Severe
Beverage dispensing equipment (no carbonator)	Minor
Beverage dispensing equipment (with carbonator)	Moderate
Bidet	Moderate to severe
Bottle washer	Moderate to severe
Bread making equipment	Minor to moderate
Canopy washers	Severe
Carwash	Severe
Chemical feed tank	Severe
Chiller tank (closed, no chemicals)	Moderate to severe
Chiller tank (open or with chemicals)	Severe
Chlorinator	Severe
Clothes washer (residential)	Moderate
Condensate tank	Severe
Condensate tank (top feed)	Moderate
Cooking kettle (for food only)	Minor .
Cooling condenser, AC unit (solenoid downstream)	Severe
Cooling condenser, AC unit (solenoid upstream)	Minor
Cooling tower	Severe
Cuspidor	Severe
De-aerator (bottom feed)	Severe
De-aerator (top feed)	Moderate
Degreasing equipment	Severe

Table B.1 (Continued)

Table B.1 (Contin	
Source of pollution or contamination	Degree of hazard
Dental delivery system (water supply)	Minor
Dental vacuum pump	Severe
Detergent dispenser	Severe
Dipper well in ice cream parlour or restaurant	Moderate
Dish rinse unit with flex hose	Moderate
Dishwasher (commercial)	Moderate
Dishwasher (residential)	Moderate
Distiller	Minor
Dockside marine facility	Severe
Emergency eyewash/shower	Eyewash/shower to be installed upstream
Flexible shower head with hose	Minor to severe
Floor drain with flushing rim	Severe
Flush tank	Moderate
Flushing equipment device	Severe
Flushometer	Severe
Fountain, ornamental	Moderate to severe
Fountain, ornamental (chemicals added)	Severe
Fume hood	Severe
Garbage can washer	Severe
Garbage disposal unit	Severe
Heat exchanger (see Annex F and Clause 5.10)	Minor to severe
Hose connection (other than residential)	Moderate to severe
Hose connection (residential)	Minor to moderate
Hospital (active treatment area)	Severe
Hospital (non-treatment area)	Moderate
Hot tub or spa	Moderate
Hot water systems (all types — direct heating of water supply) (see Annex F and Clause 5.10)	Minor
Humidifier	Moderate
Humidifier with sump (chemicals added)	Severe
Hydrotherapy bath	Moderate
Ice machine for commercial restaurant	Moderate to severe
Ice making equipment for sports arena	Severe
Industrial fluid system	Severe
Irrigation system (chemicals injected)	Severe
Irrigation system (no chemicals injected)	Moderate

Table B.1 (Continued)

Source of pollution or contamination	Degree of hazard
Lab bench equipment (non-toxic)	Minor
Lab bench equipment (toxic)	Severe
Lab faucet	Moderate to severe
Laboratory	Severe
Laundry machine	Moderate
Lavatory	Moderate
Lethal substance	Severe
Livestock equipment	Severe
Mixing tee with steam and water	Moderate
Mortuary or morgue	Severe
Non-potable water	Severe
Optician or ophthalmology equipment	Minor to moderate
Pedicure chair	Moderate to severe
Photo lab sink	Severe
Pipette washer	Severe
Piping to chemical dispensers	Minor to severe
Plating tank	Severe
Potato peeler	Moderate
Poultry barn	Severe
Pressure washer (no aspirator)	Minor
Pressure washer (with aspirator)	Severe
Private fire hydrants	Moderate
Private water source	Severe
Pump primer line (non-toxic)	Moderate
Pump primer line (toxic)	Severe
Radiator flushing equipment	Severe
Restricted area	Severe
Residential reverse osmosis equipment	Minor
Reverse osmosis equipment with backwashing	Moderate
Reverse osmosis equipment with chemical cleaning	Severe
Serrated faucets	Severe
Sewage ejectors	Severe
Sewage pump	Severe
Shampoo sinks	Moderate
Sizing vats	Severe

Table B.1 (Concluded)

Source of pollution or contamination	Degree of hazard
Solar hot water systems (residential — no chemicals added) (see Annex F and Clause 5.10)	Minor to moderate
Solar hot water systems (residential — relatively harmless heat transfer fluid) (see Annexes F, G and Clause 5.10)	Minor to moderate
Solar hot water systems (residential — toxic heat transfer fluid) (see Annexes F, G and Clause 5.10)	Severe
Solar hot water systems (commercial — single wall heat exchangers) (see Annex F and Clause 5.10)	Moderate to severe
Solar hot water systems (all types — double walled heat exchangers) (see Annex F and Clause 5.10)	Minor
Solar hot water systems (make-up water connection to the heat transfer fluid piping loop) (see Annex F and Clause 5.10)	Minor to severe
Solution tanks	Severe
Spa or hot tub	Moderate
Specimen tank	Severe
Steam boiler	Severe
Steam cleaner	Moderate
Steam generator	Moderate
Steam table	Minor to moderate
Sterilizer (condensate cooling only)	Moderate
Sterilizer (connection into chamber)	Severe
Still	Minor
Swimming pool (direct connection)	Moderate
Swimming pool (other than residential)	Moderate
Swimming pool (residential)	Minor
Swimming pool makeup tank	Moderate
Teeth cleaning equipment (veterinary type)	Moderate
Trap primer	Severe
Vending machine with no carbonators	Minor
Wash rack	Severe
Wash tank	Moderate
Wash tanks (toxic)	Severe
Water closet (flushometer type)	Moderate
Water closet (tank type)	Moderate
Water hauling equipment (see Annex C)	Severe
Water softener (residential)	Minor
Water softener drain (residential)	Moderate
Wok table (for Oriental cooking) with submerged inlet	Moderate
X-ray equipment	Severe

Table B.2 Guide to degree of hazard — Premises (See Clauses 5.3.1.2, 5.3.4.2, 5.3.4.3, and B.2.)

Type of building or facility	Degree of hazard
Airport	Moderate '
Animal feed lot	Moderate to severe
Animal stock yard	Moderate to severe
Apartment building	Moderate
Aquaculture farm	Severe
Aquarium (public)	Severe
Arena	Moderate
Asphalt plant	Severe
Auto body shop	Severe
Auto dealership	Moderate
Automotive repair	Severe
Automotive repair shop	Severe
Beverage processing plant (includes distillery and brewery)	Severe
Blood clinic	Severe
Campsite	Moderate
Campsite with RV hook-ups or dump-stations	Severe
Carwash	Severe
Chemical plant	Severe
Church	Minor to moderate
College	Moderate
Commercial premises	Moderate to severe
Concrete plant	Severe
Dental office	Moderate
Dental surgery facility	Severe
Dock and marine facility	Severe
Dry cleaning plant	Severe
Duplex housing with shared service	Minor
Dye plant	Severe
Exhibition ground	Severe
Farm	Moderate to severe
Film processing facility	Severe
Fire station	Moderate to severe
Fish farms or hatchery	Severe
Food processing plant	Severe
Fuel dispensing facility	Moderate

Table B.2 (Continued)

Table B.2 (Continued	
Type of building or facility	Degree of hazard
Funeral home	Moderate to severe
Garbage transfer facility	Severe
Golf course	Moderate to severe
Grocer	Moderate
Hair salon	Moderate
Hospital	Severe
Hotel	Moderate
Industrial and institutional premises	Moderate to severe
Kennel	Moderate
Laboratory	Severe
Laundry (commercial)	Severe
Laundry (commercial, coin-operated)	Moderate
Manufacturing plant (not specified)	Moderate
Marina (pleasure-boat)	Moderate to severe
Meat packing plant	Severe
Medical clinic (non surgical)	Moderate
Medical clinic (surgical)	Severe
Milk processing plant	Severe
Mining facility	Severe
Mobile home park	Moderate
Mortuary or morgue	Severe
Motel	Moderate
Motorcycle repair facility	Severe
Multi-service interconnected facility	Moderate
Multi-tenant single-service facility	Moderate
Nursing home	Moderate
Office building	Moderate
Oil refinery	Severe
Paint manufacturing plant	Severe
Penitentiary	Moderate
Petroleum processing or storage facility	Severe
Pharmaceutical manufacturing facility	Severe
Photo processing facility	Severe
Plants using radioactive material	Severe
Plastic manufacturing plant	Severe

Table B.2 (Concluded)

Type of building or facility	Degree of hazard
Plating shop and plant	Severe
Poultry farm	Severe
Power generating facility	Severe
Premises where access is prohibited or restricted	Severe
Printing plant	Severe
Pulp and/or paper plant	Severe
Radiator shop	Severe
Recycling facility	Severe
Refinery, petroleum processing	Severe
Rendering facility	Severe
Research building	Severe
Residential premises	Minor
Restaurant	Moderate
School (elementary, junior high, and senior high)	Moderate
Sewage dump station	Severe
Sewage treatment plant	Severe
Shopping mall	Moderate
Steam plant	Severe
Steel manufacturing plant	Severe
Swimming pool facility	Moderate
Townhouse (shared services)	Minor
Trackside facility for trains	Severe
University	Moderate to severe
Veterinary clinic	Moderate to severe
Waste disposal plant	Moderate to severe
Wastewater facility	Severe
Wastewater pump station	Severe
Wastewater treatment plant	Severe
Water filling station	Severe
Water park	Moderate
Water treatment plant	Severe
Water treatment pump station	Severe
Zoo	Severe